



PRODUCT SPECIFICATIONS



WORTHEN COATED FABRICS LABEL GROUP

STYLE WB-640W

DESCRIPTION: Nonwoven Cellulose/Polyester Blend

SPECIFICATIONS:

Total Weight: 2.76 ± 0.05 oz./sq. yd.

Thickness: 0.0082 ± 0.001 in.

Stiffness MD: 80 ± 20 mg.

CD: 30 ± 10 mg.

Opacity: 88%

Tear Strength MD: 314 ± 20 gm.

CD: 428 ± 20 gm

GENERAL: Coated with urethane on both sides. Suited for conversion into permanent care labels. Meets AATCC IVA wash test requirements. Excellent punching and scoring properties.

Recommended

Printing Methods: Thermal Transfer, Flexography, Hot Stamping, and Dot Matrix.

ALL VALUES SHOWN ARE AVERAGE VALUES OBTAINED FROM COMMERCIAL PRODUCTION. THEY ARE INTENDED AS A GUIDE TO PRODUCT PROPERTIES AND NOT TO BE REGARDED AS SHIPPING SPECIFICATIONS.



Worthen Coated Fabrics Label Group
Worthen Industries
134 Buckley SW
Grand Rapids, MI 49503

Tel: (616) 742-8990
Fax: (616) 742-8995
www.worthenindustries.com