



PRODUCT SPECIFICATIONS



WORTHEN COATED FABRICS LABEL GROUP

STYLE WS-241W

DESCRIPTION: Nonwoven Cellulose / Polyester Blend

SPECIFICATIONS:

Total Weight: 3.17 ± 0.1 oz./sq. yd.
Thickness: 0.0077 ± 0.0005 in.
Stiffness MD: 80 ± 20 mg.
CD: 30 ± 10 mg.
Opacity: 88%
Tear Strength MD: (min) 200 gm.
CD: (min) 320 gm.

GENERAL: Coated with acrylic on both sides. Suited for conversion into permanent care labels. Meets AATCC IVA wash test requirements. Exhibits excellent punching capabilities.

Recommended

Printing Methods: Flexography, Screen Printing, Offset, Hot Stamping, and Dot Matrix.

ALL VALUES SHOWN ARE AVERAGE VALUES OBTAINED FROM COMMERCIAL PRODUCTION. THEY ARE INTENDED AS A GUIDE TO PRODUCT PROPERTIES AND NOT TO BE REGARDED AS SHIPPING SPECIFICATIONS.



Worthen Coated Fabrics Label Group
Worthen Industries
134 Buckley SW
Grand Rapids, MI 49503

Tel: (616) 742-8990
Fax: (616) 742-8995
www.worthenindustries.com