



WORTHEN COATED FABRICS LABEL GROUP

STYLE PS-650-1WHS

DESCRIPTION: Woven Polyester, Heat Seal Coated

SPECIFICATIONS:

Base Denier: 70
Total Weight: 5.50 ± 0.20 oz./sq. yd.
Thickness: 0.0062 ± 0.0006 in.
Stiffness MD: 44 ± 2 mg.
CD: 44 ± 2 mg.
Opacity: 93%
Tear Strength MD: 200 ± 20 gm.
CD: 208 ± 20 gm.

GENERAL: Coated with urethane on both sides. Suited for conversion into permanent care labels. Meets AATCC IVA wash test requirements. Ravel proof edges. This product has an extra smooth surface on one side for thermal printing, and exhibits an exceptionally soft hand.

The heat seal adhesive is applied at 3 mils thickness. Recommended adhesive application conditions are a temperature of 325 - 375 F, under light pressure for 2 to 6 seconds. The adhesive has excellent bond strength to cottons, poly/cottons, and polyester fabrics, and demonstrates excellent wash and dry cleaning resistance.

Recommended

Printing Methods: Thermal Transfer, offset, flexography, and hotstamp.

ALL VALUES SHOWN ARE AVERAGE VALUES OBTAINED FROM COMMERCIAL PRODUCTION. THEY ARE INTENDED AS A GUIDE TO PRODUCT PROPERTIES AND NOT TO BE REGARDED AS SHIPPING SPECIFICATIONS.



Worthen Coated Fabrics Label Group
Worthen Industries
134 Buckley SW
Grand Rapids, MI 49503

Tel: (616) 742-8990
Fax: (616) 742-8995
www.worthenindustries.com